

THE
Honey^M
 FRAMED 60 LAYOUT MODULE



60 LAYOUT
 MONOCRYSTALLINE MODULE

325-340W
 POWER OUTPUT RANGE

19.9%
 MAXIMUM EFFICIENCY

0~+5W
 POSITIVE POWER TOLERANCE

Product DD06M.08(II) | Color of BS White | Power Range 325 -340W

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 OHSAS 18001: Occupation Health and Safety Management System



High power mono perc

- Up to 340W front power and 19.9% module efficiency with half-cut and MBB (Multi Busbar) technology bringing more BOS savings
- Lower resistance of half-cut and good reflection effect of MBB ensure high power



High reliability

- Ensured PID resistance through cell process and module material control
- Resistant to salt, acid and ammonia
- Certified to 5400 Pa positive load and 2400 Pa negative load




High energy generation


- Excellent IAM and low light performance validated by 3rd party with cell process and module material optimization
- Lower temp coefficient (-0.36%) and NMOT bring more energy leading to lower LCOE
- Better anti-shading performance and lower operating temperature

PERFORMANCE WARRANTY


10 Year Product Warranty · 25 Year Power Warranty




DIMENSIONS OF PV MODULE(mm)



I-V CURVES OF PV MODULE(340W)



P-V CURVES OF PV MODULE(340W)



ELECTRICAL DATA (STC)

Peak Power Watts-P _{MAX} (Wp)*	325	330	335	340
Power Output Tolerance-P _{MAX} (W)	0 ~ +5			
Maximum Power Voltage-V _{MPP} (V)	33.6	33.8	34.0	34.2
Maximum Power Current-I _{MPP} (A)	9.67	9.76	9.85	9.94
Open Circuit Voltage-V _{OC} (V)	40.4	40.6	40.7	41.1
Short Circuit Current-I _{SC} (A)	10.3	10.4	10.5	10.6
Module Efficiency η_m (%)	19.1	19.4	19.7	19.9

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
 *Measuring tolerance: \pm 3%.

ELECTRICAL DATA (NMOT)

Maximum Power-P _{MAX} (Wp)	246	250	254	257
Maximum Power Voltage-V _{MPP} (V)	31.6	31.7	31.9	32.1
Maximum Power Current-I _{MPP} (A)	7.79	7.86	7.94	8.01
Open Circuit Voltage-V _{OC} (V)	38.1	38.3	38.4	38.7
Short Circuit Current-I _{SC} (A)	8.30	8.38	8.46	8.54

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	120 cells (6 \times 20)
Module Dimensions	1698 \times 1004 \times 35 mm (66.85 \times 39.53 \times 1.38 inches)
Weight	18.7kg (41.2lb)
Glass	3.2mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm (1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: N 140mm/P 285mm(5.51/11.22inches) Landscape: N 1200 mm /P 1200 mm (47.24/47.24 inches)
Connector	MC4 / TS4

TEMPERATURE RATINGS

NMOT (Nominal Module Operating Temperature)	41 C (\pm 3 C)
Temperature Coefficient of P _{MAX}	- 0.36%/ C
Temperature Coefficient of V _{OC}	- 0.26%/ C
Temperature Coefficient of I _{SC}	0.04%/ C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

MAXIMUM RATINGS

Operational Temperature	-40~+85 C
Maximum System Voltage	1000V DC (IEC) 1000V DC (UL)
Max Series Fuse Rating	20A

WARRANTY

10 year Product Workmanship Warranty
25 year Power Warranty

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 30 pieces
Modules per 40' container: 780 pieces